

Dockerfile

```
FROM openjdk: 8
VOLUME /tmp
# EXPOSE 80
ENV TZ=Asia/Shanghai JAVA_OPTS=-Xmx512m
RUN ln -snf /usr/share/zoneinfo/$TZ /etc/localtime && echo $TZ > /etc/timezone
ADD *.jar app.jar
ENTRYPOINT java $JAVA_OPTS -Djava.security.egd=file:/dev/./urandom -jar /app.jar
# ENTRYPOINT exec java $JAVA_OPTS -Djava.security.egd=file:/dev/./urandom -jar /app.jar --
Dspring.config.location=/config/*
# Tomcat java.security.egd /dev/urandom ENTRYPOINT
ENTRYPOINT ['java', $JAVA_OPTS, '-Djava.security.egd=file:/dev/./urandom', '-jar', '/app.jar',
'--Dspring.config.location=/config/*']

FROM java: 8
VOLUME /tmp
EXPOSE 8080
ENV TZ=Asia/Shanghai JAVA_OPTS=-Xmx512m
RUN ln -snf /usr/share/zoneinfo/$TZ /etc/localtime && echo $TZ > /etc/timezone
ADD *.jar app.jar
ENTRYPOINT java $JAVA_OPTS -Djava.security.egd=file:/dev/./urandom -jar /app.jar

#
FROM openjdk: 11
VOLUME /tmp
ENV TZ=Asia/Shanghai JAVA_OPTS=-Xmx512m
RUN ln -snf /usr/share/zoneinfo/$TZ /etc/localtime && echo $TZ > /etc/timezone
ADD *.jar app.jar
# CMD echo '10.254.7.7 bzdt.s.chinaetc.org' >> /etc/hosts; java $JAVA_OPTS -
Djava.security.egd=file:/dev/./urandom -jar /app.jar --Dspring.config.location=/config/*
ENTRYPOINT echo '10.254.7.7 bzdt.s.chinaetc.org' >> /etc/hosts && java $JAVA_OPTS -
Djava.security.egd=file:/dev/./urandom -jar /app.jar --Dspring.config.location=/config/*

# tomcat_8.5.47-jdk11
FROM tomcat: 8.5.47-jdk11
```

```
# MAINTAINER itqmdx@gmail.com
# VOLUME /usr/local/tomcat
EXPOSE 8080
# RUN rm -rf /usr/local/tomcat/webapps/*
ENV TZ=Asia/Shanghai JAVA_OPTS=-Xmx512m
RUN ln -snf /usr/share/zoneinfo/$TZ /etc/localtime && echo $TZ > /etc/timezone
# ADD ./target/* /usr/local/tomcat/webapps/
ENTRYPOINT [' /usr/local/tomcat/bin/catalina.sh', 'run']
# ENTRYPOINT echo '10.254.7.7 bzds.chinaetc.org' >> /etc/hosts &&
/usr/local/tomcat/bin/catalina.sh run
```

Revision #1

Created 16 March 2020 04:52:24 by

Updated 16 March 2020 04:53:19 by